

09-19-00

Case Docket No. PHD 99,127

jc321 U.S. PTO
09/663594

09/16/00

THE COMMISSIONER FOR PATENTS, Washington, D.C. 20231

Enclosed for filing is the patent application of Inventor:
WOLFGANG O. BUDDÉ, MANFRED ZINKE and PETER FUHRMANN**FOR:** NETWORK COMPRISING A PLURALITY OF NETWORK NODES AND AT LEAST
ONE STAR NODE**ENCLOSED ARE:**

- ☒ Appointment of Associates;
☒ Information Disclosure Statement, Form PTO-1449 and copies of documents listed therein;
☒ Preliminary Amendment;
☒ Specification (13 Pages of Specification, Claims, & Abstract);
☒ Declaration and Power of Attorney:
 (2 Pages of a [] fully executed [X] unsigned Declaration);
☒ Drawing (6 sheets of [] informal [X] formal sheet);
☒ Certified copies of German Application Serial nos. 19944597.4 and 19944596.6;
☒ Authorization Pursuant to 37 CFR §1.136(a) (3)
☐ Other: ;
☐ Assignment to

FEE COMPUTATION

CLAIMS AS FILED				
FOR	NUMBER FILED	NUMBER EXTRA	RATE	BASIC FEE - \$690.00
Total Claims	11 - 20 =		X \$18 =	0.00
Independent Claims	3 - 3 =		X \$78 =	0.00
Multiple Dependent Claims, if any			\$260 =	0.00
TOTAL FILING FEE			=	\$ 690.00

Please charge Deposit Account No. 14-1270 in the amount of the total filing fee indicated above, plus any deficiencies. The Commissioner is also hereby authorized to charge any other fees which may be required, except the issue fee, or credit any overpayment to Account No. 14-1270.


[] Amend the specification by inserting before the first line as a centered heading --Cross Reference to Related Applications--; and insert below that as a new paragraph --This is a continuation-in-part of application Serial No. , filed , which is herein incorporated by reference--.

CERTIFICATE OF EXPRESS MAILING

Express Mail Mailing Label No. EL 458 219 436 US
 Date of Deposit: September 18, 2000
 I hereby certify that this paper and/or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 C.F.R. 1.10 on the date indicated above and is addressed to the Commissioner of Patents and Trademarks, Washington, D.C. 20231.

Patricia DeMichele
 Typed Name

Signature


 Steven R. Biren, Reg.No. 26,531
 Attorney
 (914) 333-9630
 U.S. Philips Corporation
 580 White Plains Road
 Tarrytown, New York 10591

09/18/00
jc321 U.S. PTO
09/663594

09653594.091300

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of

Atty. Docket

WOLFGANG O. BUDDE ET AL

PHD 99,127

Serial No.

Filed: CONCURRENTLY

NETWORK COMPRISING A PLURALITY OF NETWORK NODES AND AT LEAST ONE
STAR NODE

Honorable Commissioner of Patents and Trademarks
Washington, D.C. 20231

PRELIMINARY AMENDMENT

Sir:

Prior to calculation of the filing fee and examination, please
amend the above-identified application as follows:

IN THE TITLE

Please change the Title to all Capital Letters.

IN THE SPECIFICATION

Page 1, before line 1, insert as a centered heading:

--BACKGROUND OF THE INVENTION--;

between lines 10 and 11, insert as a centered heading:

--SUMMARY OF THE INVENTION--;

Page 3, before line 1, insert as a centered heading:

--BRIEF DESCRIPTION OF THE DRAWING--;

between lines 16 and 17, insert as a centered heading:

--DESCRIPTION OF THE PREFERRED EMBODIMENTS--;

IN THE CLAIMS

Page 10, before line 1, replace "CLAIMS:" with

--WHAT IS CLAIMED IS:--

IN THE ABSTRACT

Before line 1, delete "ABSTRACT:" and substitute the following
as a centered heading:

--ABSTRACT OF THE DISCLOSURE--;


last line, delete "Fig 1".

REMARKS

The Abstract and Specification have been amended to add
headings in accordance with MPEP Section 601 and place the instant
application in standard U.S. format.

Entry of this amendment prior to calculating the filing
fee is respectfully requested.

Respectfully submitted,

By 
Steven R. Biren, Reg. 26,531
Attorney
(914) 333-9630
September 15, 2000

Network comprising a plurality of network nodes and at least one star node

The invention relates to a network comprising a plurality of network nodes. Such networks may be installed, for example, in private cars, in industrial automation (for example, sensor systems) and domestic automation (for example, lighting, alarm systems, heating system, air-conditioning system, etc.).

5 In such a network for private cars can be used, for example, the TTP protocol (TTP = Time-Triggered Protocol) known from the journal "Elektronik", No. 14, 1999, pp. 36 to 43 (Dr. Stefan Blenda, Georg Kroiss: "TTP: "Drive by Wire" in greifbarer Nähe"). This protocol makes a reliable data transmission possible and may therefore also be used in networks concerning safety devices (for example brakes). Said article mentions a bus system
10 as a network structure.

It is an object of the invention to provide a different network comprising more network nodes.

The object is achieved by a network of the type defined in the opening paragraph,

15 in that at least part of the network nodes are directly intercoupled via at least one star node, in that the star node contains a plurality of star interfaces which are assigned to at least one network node and in that, in dependence on a pilot signal, one star interface always conveys a message from the assigned network node to the other star interfaces, or from another star interface to at least
20 one of the assigned network nodes.

The underlying idea of this invention is the control of a star node by means of a pilot signal which is generated by the network nodes. The pilot signal is changed before and after a transmission of a message in that a star interface contained in the star node and assigned to a network node detects when the assigned network node changes the pilot signal.

25 In the star node the other star interfaces are then switched, so that they receive only a message from the star interface that receives a message from the assigned network node.

The star interfaces provide a correct line terminal at the input of a star interface and by means of the pilot signal an unambiguous control of the traffic of messages.

As shown in patent claim 2, each network node in the network is assigned a certain periodically recurrent time section for the transmission of its messages. The pilot signal generator in a network node signalizes this time section when a pilot signal is transmitted. The pilot signal may be distinguished from the actual message in various ways.

- 5 For example, the pilot signal uses a different frequency range from the signal having the message to be transmitted.

- Patent claim 3 indicates that each star interface contains a first and a second switch element and a pilot signal detector. The switch elements, which, as described in claim 3, may be a switchable amplifier, control the flow of messages in a star interface in
10 dependence on the pilot signal.

During the transmission of messages, which is indicated by the pilot signal, a star interface generates a release signal which is applied to the other star interfaces via an OR combination, as described in claim 5. Claim 6 indicates that the OR combination may be arranged as an OR gate or as a wired OR combination.

- 15 The use of a pilot signal for controlling the traffic of messages makes the optional addition of redundant line connections possible, so that for each additional line connection a further star interface is added. Furthermore, for each additional line connection the network node is extended by one circuit component for transmitting a message combined with a pilot signal and for receiving such a message. An additional control is necessary for
20 detecting defects and selecting a line connection.

For example, with symmetrical signal transmission a line connection may be a line pair.

- The invention relates to a network node, which is characterized
in that the network node is provided for the coupling to further network nodes via at least one
25 star node, and
in that for the coupling to further network nodes the network node has a pilot signal to indicate a message transmission to a star interface of the star node.

- Furthermore, the invention relates to a star node in a network for coupling a plurality of network nodes to a plurality of star interfaces which are assigned at least to one
30 network node and which, always in dependence on a pilot signal, are arranged for conveying a message from the assigned network node to the other star interfaces, or from another star interface to at least one of the assigned network nodes.

Examples of embodiment will be explained with reference to the Figures.

In the drawings:

Fig. 1 shows a network in a star structure, comprising a plurality of network nodes, which are coupled via an active star node,

Fig. 2 shows a first embodiment of a star interface in a star node,

Fig. 3 shows a first embodiment of a first star node,

Fig. 4 shows part of a network node comprising a pilot signal generator,

Fig. 5 shows part of a time diagram of two signals in the network,

Figs. 6 and 7 show two further embodiments of the network,

Fig. 8 shows a second embodiment of a star interface in a star node,

Fig. 9 shows a second embodiment of a first star node,

Fig. 10 shows an embodiment of a network comprising additional redundant components, and

Fig. 11 shows a further embodiment of part of a network node comprising two pilot signal generators, pilot signal detectors and one controller.

An example of embodiment of the network according to the invention is shown in Fig. 1. This network contains, for example, four network nodes 1 to 4, which are intercoupled via an active star node 9 through line pairs (twisted pairs) 5 to 8 provided for a symmetrical signal transmission. The active star node 9 performs a line adaptation, so that the line pairs 5 to 8 in the active star node 9 are terminated by a wave resistor, and detects a pilot signal transmitted by a network node 1 to 4. If the line pairs 5 to 8 were interconnected without the active star node 9, there would be a mismatch in the neutral point for each line pair as a result of the impedance jump from Z_0 to $1/3Z_0$, which is caused by the fact that the respective other line pair is connected in parallel. For generating a pilot signal, each network node 1 to 4 further includes a pilot signal generator.

The active star node 9 contains for each line pair 5 to 8 a star interface which enables a transfer of the messages from a transmitting network node to all the other network nodes connected to the active star node. An example of embodiment of such a star interface is shown in Fig. 2. A line pair 5 to 8 is connected to the inputs of a switchable amplifier 10, to the outputs of a further switchable amplifier 11, to a pilot signal detector 12 and to a terminal resistor 13. The value of the terminal resistor 13 corresponds to the wave resistance and is therefore used for the correct line termination. When the pilot signal detector 12

detects a pilot signal, it generates a release signal which is led to a switch input 14 of the switchable amplifier 10, to an inverting input of an AND gate 15 and, via an amplifier 17 and a line 18, to an OR gate 23 (Fig. 3). When the switchable amplifier 10 has been released, it supplies data to a data line 19, which leads to a switching point. This data line 19 also receives data from the other star interfaces and transfers them via the switchable amplifier 11 to the assigned line pair. Via a line 20 the non-inverting input of the AND gate 15 is supplied with a release signal produced by another star interface, via the OR gate 23 (Fig. 3). The non-inverting output of the AND gate 15 is connected to a switch input 21 of the switchable amplifier 11 and, via an inverter 16, to a release input 22 of the pilot signal detector.

A switchable amplifier 10 or 11 may also be arranged as a series combination of amplifier and switch (switch element). In the closed state of this switch, the output signal of the amplifier is transmitted.

The pilot signal detector detects whether the assigned network node shows, by transmitting the pilot signal, that it intends to transmit messages or data, respectively. If this is the case, the amplifier 11 is deactivated (generally it will already have reached this state) and the amplifier 10 is activated or released. The message signal coming from the assigned line pair is led to the line 19 and transferred there to the other star interfaces. Additionally, the release signal generated by the pilot signal detector 12 signalizes the other star interfaces that they are to activate or release their respective amplifier 11 in order to transfer the messages to the respective assigned network nodes.

As shown in Fig. 3, the lines 18 of all the star interfaces are combined in the OR gate 23. Furthermore, Fig. 3 shows four star interfaces 24 to 27 which are respectively coupled to the line pairs 5 to 8. The output of the OR gate 23 is connected to the lines 20 (Fig. 2) of the star interfaces 24 to 27. Lines 19 (Fig. 2) of the star interfaces 24 to 27 are combined via a circuit node 28.

To avoid a signal coming from a line pair 5 to 8 again being returned to the same pair, the amplifier 11 is deactivated or switched off via the inverting input of the AND gate 15. On the other hand, to avoid the pilot signal detector assigned to another network node activating its own amplifier 10, the release signal transported over the line 20 (Fig. 2) is used via AND gate 15 and inverter 16 to suppress the release signal for the pilot signal detector 12. This also switches off or deactivates the amplifier 10 via its switch input 14. The pilot signal detector 12, whose pilot signal causes the assigned star interface to receive data, however, remains active for detecting the end of the data transmission.

For the perfect functioning of the active star node 9 it is necessary that the network nodes 1 to 4 transmit their messages not overlapping with time. In addition, it is to be ensured that for the duration of a certain dead time no network node is active or transmits messages or data, respectively. In this state the star node is fully blocked (i.e. all the amplifiers 10 and 11 are deactivated). In this state a star interface 24 to 27 in the star node 9 waits for a new pilot signal, by which a request for transmitting messages is indicated. Basically it holds that the pilot signal is always to be transmitted ahead of the beginning of the transmission of the actual message. Only then will it be ensured that the active star node 9 is timely configured and that also the beginning of the message reaches all the other network nodes.

Fig. 4 shows in what manner the pilot signal is generated in a network node 1 to 4 and transmitted over a line pair 5 to 8. When a network node wishes to transmit a message or data to other network nodes, a pilot signal generator 29 receives for example a star signal over a line 30. The pilot signal generator 29 then delivers a pilot signal to a multiplexer 31 to which data to be transmitted are supplied via a line 32. The signal produced by the multiplexer 31 is applied to the assigned line pair via an amplifier 33. A signal originating from another network node is led by the line pair via an amplifier 34 onto a line 35 for further processing.

The multiplexer shown in Fig. 4 may then be arranged both as a time multiplexer (transmission of the pilot signal as a start and a stop signal each time before and after the actual message), or as a frequency multiplexer. This means that the pilot signal may accompany either as a continuous signal the whole message to be transmitted, or that it can be transmitted in the form of a start and a stop signal. For example, as a result of different durations, there may then be ensured that the start and the stop signal are sufficiently distinguished and the change between transmission time and transmission pause is not mixed up.

The pilot signal may be generated in various ways. One possibility is that it may be a periodic signal, whose frequency range lies outside the frequency range used for the transmission of the messages. This frequency range may lie above or below the useful frequency band, but also in "gaps" of the effective frequency band. A further possibility is to transmit the actual message as a symmetrical push-pull signal and the pilot signal as an in-phase signal. The in-phase signal may be in the form of a constant voltage, but also in the form of a periodic signal. A third possibility for the pilot signal is that it is realized in the form of special symbols put before or after the transmitted message.

The proposed invention is particularly suitable for use in networks operating according to the TTP protocol for a real-time communication, for example, in private cars (compare Elektronik Heft 14/1999: "TTP: "Drive by Wire" in greifbarer Nähe" pp. 36 to 43). With this protocol there is determined, on the one hand, when which transmitter is allowed to transmit with the aid of the conflict-free TDMA access method (TDMA = time-division multiple access) and, on the other hand, a dead time (interframe gap) is defined in which no transmitter is allowed to transmit. This mechanism immediately guarantees that the active star node 9 always goes back to the state of rest. Thus the TDMA method guarantees that always only one network node is allowed to transmit a message at a predefined time and, for this purpose, by means of the pilot signal transmitted by it activates or causes to activate in the star node the star interface assigned thereto to transfer messages.

An additional advantage is that for controlling the so-called bus guardian, a control signal is to be present in the network node, which signal lies shortly before the beginning of the transmission of the message. This control signal may be used directly for controlling the pilot signal generator 29 in that this control signal is applied to the pilot signal generator 29 over the line 30.

In Fig. 5, this control signal is referenced BG and the actual message is referenced data. The control signal BG is, for example, in a low state during the transmission of a message. During this low state of the control signal the message is to be transmitted. A first time space T1, after a change of the control signal to the low state, and a second time space T2, before a change of the control signal to the high state, are then to be selected so that the active star node 9 is and continues to be configured correctly for the flawless transmission of a message. It is still to be observed that the TTP protocol supports different (constant) message delay times between various network nodes in the network. So doing, the delay time caused by the active star node 9 does not violate the TTP protocol.

The network according to the invention enables the transmission of a pilot signal with any type of signal transmission for the messages from a network node 1 to 4. For example, for the transmission of messages a symmetrical push-pull transmission, single line transmission or carrier frequency-modulated transmission can be selected. With an in-phase coupling of the line pairs 5 to 8 could be transmitted a supply voltage, for example, together with the transmission of a message.

A further example of embodiment of a network is shown in Fig. 6. This network is almost identical with the network shown in Fig. 1 (network nodes 1 to 4 and line pairs 5 to 8), except for four additional network nodes 36 to 39. The network node 36 is

coupled directly to the active star node 9 via a further line pair 40. The network node 37 is connected to the line pair 5 via a line pair 41. The network node 38 is connected to the line pair 8 via a line pair 42 and the network node 39 to the line pair 42 via a line pair 43.

The example of embodiment shown in Fig. 7 again shows the topology of the network known from Fig. 1 with the network nodes 1 to 4, the line pairs 5 to 8 and the active star node 9. The active star node 9 is coupled via a line pair 44 to a further active star node 45 to which further network nodes may be connected. For example, a network node 46 is drawn in here.

In lieu of the OR gate 23 necessary in Fig. 3, this OR combination may also be realized directly by a wired OR combination. A star interface suitable for the wired OR combination is shown in Fig. 8. This star interface as shown in Fig. 8 is identical with the star interface of Fig. 2 except for the switched combination of the output of the amplifier 17. In Fig. 8 the output of the amplifier 17 does not lead to the line 18, but to the line 20 (wired-OR). This provides that the output of the amplifier 17 is connected to the inverting input of the AND gate 15. The amplifier 17 is realized in Fig. 2 as a push-pull amplifier and in Fig. 8 as an open-collector or open-drain amplifier, respectively.

As a result of this wired OR combination, the cost of wiring is reduced and the OR gate 23 is omitted from the active star node and the network can easily be extended by further network nodes as a result of the omission of the OR gate, which is otherwise to be maintained in some variants. The star interfaces 24 to 27 are in this case connected to their respective lines 19 and 20 so that, as a result, they form two circuit nodes 47 and 48 as shown in Fig. 9. Only one resistor 49 is additionally to be provided, which is coupled, on the one hand, to the circuit node 47 and, on the other, to a supply voltage. Together with the amplifiers 17 of each star interface, this resistor forms the wired OR combination.

To enhance the availability of network nodes in a network, a plurality of line pairs and thus the assigned circuit components for generating a pilot signal (compare Fig. 4) are doubled, as is shown in Fig. 10. The network shown in Fig. 10 contains four network nodes 50 to 53 and one star node 54. The network nodes 50 and 51 are coupled to the star node 54 via respective line pairs 56 and 57 and the network nodes 52 and 53 are coupled to the star node 54 via two respective line pairs 58 to 61. This means that the network node 52 is connected to the star node 54 via the line pair 58 and 59 and the network node 53 via the line pair 60 and 61.

Fig. 11 shows how a pilot signal is generated in a network node 52 and 53 and is transmitted over a line pair 64 or 65. For generating a pilot signal are used the pilot signal

generators 66 and 67. The sending of a control signal over the lines 68 or 69 from a control unit 82 determines which pilot signal generator (66 or 67) generates a pilot signal. The pilot signal generator 66 or 67 delivers such a pilot signal to an associated multiplexer 70 or 71, respectively. The multiplexer 70 or 71 respectively, receives a message or data over a line 72 or 73. The output signal of the multiplexer 70 or 71 respectively, is applied to the respective line pair 64 or 65 via a switchable amplifier 74 or 75.

Data originating from the star node 54 are sent to an amplifier 76 or 77 via the line pair 64 or 65, respectively. The amplifier 76 or 77 delivers the data over a line 78 or 79 respectively, to further circuit components of the network node.

To the output of each amplifier 76 or 77 is connected a respective pilot signal detector 80 or 81. When a pilot signal detector 80 or 81 has detected a pilot signal, a control unit 82 (state machine) is informed thereof. This control unit 82 controls the two switchable amplifiers 74 and 75. Furthermore, the control unit 82 controls the pilot signal generators 66 and 67 over the lines 68 and 69. The start signal already mentioned above coming from the network node is led over a line 83 to the control unit 82, which forms a control signal from it for the pilot signal generators 66 and 67. The control unit 82 can report, for example, states to the network node via a line 84.

The circuit elements 66, 68, 70, 72, 74, 76, 78 and 80 form a first circuit component 85 and the circuit elements 67, 69, 71, 73, 75, 77, 79 and 81 form a second circuit component 86. The circuit components 85 and 86 have identical structures.

This control unit 82 manages the line pairs 64 and 65 connected to the network node, so that the operability of the line pairs 64 and 65 and of the circuit components 85 and 86 is tested continuously.

During the reception of a message, the control unit 82 checks whether the pilot signal has really arrived over the two line pairs 64 and 65. The arrival of a pilot signal on one of the two redundant line pairs signalizes the beginning of the reception of a message. In a certain time section the control unit 82 checks whether, after the first pilot signal has arrived on one of the line pairs 64 or 65, the pilot signal has arrived on the other line pair. If this is not the case, there may be assumed that the other line pair is defective.

Transmission basically takes place on only one of the redundant line pairs. To achieve that even if one of the circuit components 85 or 86 breaks down the communication can be kept going, during each transmission operation a check is made whether the pilot signal accompanying the message has really been transmitted. The structure of the network node ensures that the pilot signal is sent back to the transmitting network node via the very

The combination of these two checks enables to detect a defect of the circuit components 85 and 86 and line pairs 64 and 65 used at the time for the transmission of messages and to switch over the non-defective circuit components via the assigned non-defective line pair of the control unit 82.

If there is no error and thus the control unit 82 has registered the two line pairs 64 and 65 and the two circuit components 85 and 86 as working, the circuit components 85 and 86 for example alternately transmit to the assigned star interface. In the case of a defect, only the circuit component 85 or 86 registered as non-defective will transmit.

CLAIMS:

1. A network comprising a plurality of network nodes, characterized in that at least part of the network nodes are directly intercoupled via at least one star node, in that the star node contains a plurality of star interfaces which are assigned to at least one network node and
- 5 in that, in dependence on a pilot signal, one star interface always conveys a message from the assigned network node to the other star interfaces, or from another star interface to at least one of the assigned network nodes.
2. A network as claimed in claim 1, characterized in that each network node in the network is assigned a certain periodically recurrent time section for the transmission of its messages and
- 10 in that a network node comprises a pilot signal generator which generates a pilot signal which denotes either the whole assigned time section or the beginning and end of the time section.
3. A network as claimed in claim 1, characterized in that each star interface comprises a first and second switch element and a pilot signal detector,
- 15 in that the first switch element in activated state is provided for allowing a message to pass from the assigned network node to the other star interfaces and the second switch element in activated state is provided for allowing a message to pass from the other star interfaces to the assigned network node and
- 20 in that the pilot signal detector is provided for activating a first switch element and deactivating a second switch element or deactivating the first switch element and activating the second switch element in dependence on a pilot signal from the assigned network node.
4. A network as claimed in claim 3, characterized in that the first and second switch elements are each a switchable amplifier.
5. A network as claimed in claim 1, characterized in that a star interface is provided for generating a release signal when the assigned network node denotes a message

transmission by a pilot signal, in that the lines conveying the release signal of each star interface are coupled via an OR combination and in that the OR combination transfers the release signal to all the star interfaces of the star node.

5

6. A network as claimed in claim 5, characterized in that the OR combination is an OR gate or a wired OR combination.

10

7. A network as claimed in claim 2, characterized in that at least one network node is assigned a plurality of star interfaces of which only one is provided for transferring messages in dependence on the state of the assigned network node.

15

8. A network as claimed in claim 7, characterized in that at least one network node contains at least two pilot signal generators and two multiplexers for combining the pilot signal generated by the assigned pilot signal generator with a message, and in that a control unit decides over which line connection and over which assigned star interface the message combined with a pilot signal is transmitted.

20

9. A network as claimed in claim 8, characterized in that the control unit is provided for testing the operability of the star interfaces, of the line connections and of a circuit component in the network node, which switch component forms the message with the pilot signal and receives such a message,

25

in that during the reception of the message the control unit checks the presence of the pilot signal on the various line connections by evaluating pilot signal detectors, and, during the transmission of the message, the presence of the pilot signal on all the line connections, except for the line connection that transmits the message that has been transmitted.

30

10. A network node in a network comprising further network nodes, characterized in that the network node is provided for coupling to further network nodes via at least one star node and in that the network node is provided for indicating a transmission of a message to a star interface of the star node together with a pilot signal.

11. A star node in a network for coupling a plurality of network nodes to a plurality of star interfaces, which are assigned to at least one network node and which, in dependence on a pilot signal, are each provided for transferring a message from the assigned network node to the other star interfaces, or from another interface to at least one of the

5 assigned network nodes.

09663594-091800

ABSTRACT:

The invention relates to a network comprising a plurality of network nodes. At least part of the network nodes are directly intercoupled via at least one star node. The star node contains a plurality of star interfaces which are assigned to at least one network node. A star interface is provided for transferring a message from the assigned network node to the other star interfaces or from another star interface to at least one of the assigned network nodes always in dependence on a pilot signal.

Fig. 1

1/6




FIG. 1




FIG. 2

0001601250000




FIG. 3




FIG. 4

3/6




FIG. 5




FIG. 6

000000-10555500

4/6




FIG. 7




FIG. 8

0001607659300

5/6




FIG. 9




FIG. 10

09663594.091000




FIG. 11

DECLARATION and POWER OF ATTORNEY

ATTORNEY'S DOCKET NO.:
PHD 99.127 US

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

"Network comprising a plurality of network nodes and at least one star node"

the specification of which (check one)

☐ is attached hereto.

☐ was filed on _____ as Application Serial No. _____ and was amended on _____ (if applicable).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by the amendment(s) referred to above.

I acknowledge the duty to disclose information which is material to patentability of this application in accordance with Title 37, Code of Federal Regulations, §1.56(a).

I hereby claim foreign priority benefits under Title 35, United States Code, § 119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

PRIOR FOREIGN APPLICATION(S)

COUNTRY	APP. NUMBER	DATE OF FILING (DATE, MONTH, YEAR)	PRIORITY CLAIMED UNDER 35 U.S.C. 119
Germany	19944597.4	16 September 1999	YES
Germany	19944596.6	16 September 1999	YES

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35 United States Code, §112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, §1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application:.

PRIOR UNITED STATES APPLICATION(S)

APPLICATION SERIAL NUMBER	FILING DATE	STATUS (PATENTED, PENDING, ABANDONED)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. (list name and registration number)

Jack E. Haken, Reg. No. 26,902

Michael E. Marion, Reg. No. 32,266

Edward Blocker, Reg. No. 30,245

SEND CORRESPONDENCE TO: Corporate Patent Counsel; U.S. Philips Corporation; 580 white Plains Road; Tarrytown, NY 10591	DIRECT TELEPHONE CALLS TO: (name and telephone No.) (914) 332-0222
--	--

Dated:		Inventor's Signature:	
Full Name of In Inventor	Last Name BUDE	First Name Wolfgang	Middle Name O.
Residence & Citizenship	City Aachen	State of Foreign Country Germany	Country of Citizenship Germany
Post Office Address	Street Kandelfeldstrasse 41	City 52074 Aachen	State of Country Germany
			Zip Code
Dated:		Inventor's Signature:	
Full Name of In Inventor	Last Name ZINKE	First Name Manfred	Middle Name
Residence & Citizenship	City Aachen	State of Foreign Country Germany	Country of Citizenship Germany
Post Office Address	Street Aldorfstrasse 29	City 52066 Aachen	State of Country Germany
			Zip Code

Dated:		Inventor's Signature:	
Full Name of In Inventor	Last Name FUHRMANN	First Name Peter	Middle Name
Residence & Citizenship	City Aachen	State of Foreign Country Germany	Country of Citizenship Germany
Post Office Address	Street Auf der Huls 20	City 52080 Aachen	State of Country Germany Zip Code
Dated:		Inventor's Signature:	
Full Name of In Inventor	Last Name	First Name	Middle Name
Residence & Citizenship	City	State of Foreign Country	Country of Citizenship
Post Office Address	Street	City	State of Country Zip Code
Dated:		Inventor's Signature:	
Full Name of In Inventor	Last Name	First Name	Middle Name
Residence & Citizenship	City	State of Foreign Country	Country of Citizenship
Post Office Address	Street	City	State of Country Zip Code
Dated:		Inventor's Signature:	
Full Name of In Inventor	Last Name	First Name	Middle Name
Residence & Citizenship	City	State of Foreign Country	Country of Citizenship
Post Office Address	Street	City	State of Country Zip Code
Dated:		Inventor's Signature:	
Full Name of In Inventor	Last Name	First Name	Middle Name
Residence & Citizenship	City	State of Foreign Country	Country of Citizenship
Post Office Address	Street	City	State of Country Zip Code

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of

Atty. Docket

WOLFGANG O. BUDDÉ ET AL

PHD 99,127

Serial No.

Filed: CONCURRENTLY

NETWORK COMPRISING A PLURALITY OF NETWORK NODES AND AT LEAST ONE
STAR NODE

Commissioner for Patents
Washington, D.C. 20231

APPOINTMENT OF ASSOCIATES

Sir:

The undersigned Attorney of Record hereby revokes all
prior appointments (if any) of Associate Attorney(s) or Agent(s) in
the above-captioned case and appoints:


Steven R. Biren

(Registration No. 26,531)

c/o U.S. PHILIPS CORPORATION, Intellectual Property Department, 580
White Plains Road, Tarrytown, New York 10591, his Associate
Attorney(s)/Agent(s) with all the usual powers to prosecute the
above-identified application and any division or continuation
thereof, to make alterations and amendments therein, and to
transact all business in the Patent and Trademark Office connected
therewith.

ALL CORRESPONDENCE CONCERNING THIS APPLICATION AND THE
LETTERS PATENT WHEN GRANTED SHOULD BE ADDRESSED TO THE UNDERSIGNED
ATTORNEY OF RECORD.

Respectfully,



Jack E. Haken, Reg. 26,902
Attorney of Record

Dated at Tarrytown, New York
this 15TH day of SEPTEMBER 2000.